

## Specifications:

Designation	Ø Dh6		L		L1 mm	D1 mm	W mm	G	Cutter Dia. D2 (inch)
	mm	inch	mm	inch					
CT30/FMB1*/45	25.4	1	45	1.77	20	50	9.52	M12	2.5-3
CT30/FMB1*/60	25.4	1	60	2.36	20	50	9.52	M12	2.5-3
CT30/FMB11/4*/45	31.75	1¼	45	1.77	22	60	12.7	M16	4
CT40/FMB1*/45	25.4	1	45	1.77	20	50	9.52	M12	2.5-3
CT40/FMB1*/60	25.4	1	60	2.36	20	50	9.52	M12	2.5-3
CT40/FMB1*/90	25.4	1	90	3.54	20	50	9.52	M12	2.5-3
CT40/FMB1*/105	25.4	1	105	4.13	20	60	9.52	M12	2.5-3
CT40/FMB1¼"/45	31.75	1¼	45	1.77	22	60	12.7	M16	4
CT40/FMB1¼"/75	31.75	1¼	75	2.95	22	60	12.7	M16	4
CT40/FMB1¼"/90	31.75	1¼	90	3.54	25	60	12.7	M16	4
CT40/FMB11/2"/60	38.1	1½	60	2.36	26	75	15.87	M20	5-6
CT40/FMB2*/60	50.8	2	60	2.36	20	98	15.87	M24	5-6
CT50/FMB1*/45	25.4	1	45	1.77	20	50	9.52	M12	2.5-3
CT50/FMB1*/90	25.4	1	90	3.54	20	50	9.52	M12	2.5-3
CT50/FMB1*/150	25.4	1	150	5.9	20	60	9.52	M12	2.5-3
CT50/FMB11/4*/45	31.75	1¼	45	1.77	22	60	12.7	M16	4
CT50/FMB11/4*/75	37.75	1¼	75	2.95	22	60	12.7	M16	4
CT50/FMB11/4*/105	37.75	1¼	105	4.13	22	98	12.7	M16	4
CT50/FMB11/2*/45	38.1	1½	45	1.77	25	80	15.87	M20	5-6
CT50/FMB11/2*/75	38.1	1½	75	2.95	25	80	15.87	M20	5-6
CT50/FMB2*/45	50.8	2	45	1.77	26	98	19.05	M24	5-6
CT50/FMB2*/75	50.8	2	75	2.95	26	98	19.05	M24	5-6