

Specifications:

Designation	Ø D		L	E	M	H	Ø C	B	MICROBORE UNIT (CARTRIDGE AND INSERT)	APPROX. WEIGHT (kg.)
	Min.	Max.								
BT 40-BCA 13.5-105			105	8						1.5
BT 40-BCA 13.5-165	13.5	16	165	68				13		2
BT 40-BCA 14.5-105			105	8						1.5
BT 40-BCA 14.5-165	14.5	17	165	68	67	15		14	M1B2F40 (BRAZED CARBIDE TIP)	2
BT 40-BCA 16- 105			105	2						1.5
BT 40-BCA 16- 180	16	22.5	180	77	73	18		15	M1A2F40 (BRAZED CARBIDE TIP)	2
BT 40-BCA 19- 120			120	4						1.5
BT 40-BCA 19- 180	19	23	180	64	86	23	44	18	M2B2 (CCMT060204)	2
BT 40-BCA 23- 135			135	-						1.5
BT 40-BCA 23- 195	23	29	195	60	105	24		22	M3B2 (TCMT 06T104 CCMT060204)	2
BT 40-BCA 29- 150			150	5						1.5
BT 40-BCA 29- 195	29	41	195	50		30		28	M3A2 (TCMT 06T104 CCMT060204)	2
BT 40-BCA 38- 150			150	5	115			35		2
BT 40-BCA 38- 210	38	49	210	8	172	41	44	37	M5B2 (TCMT 110204 CCMT060204)	2.5
BT 40-BCA 46- 150			150	5	115			41		2.5
BT 40-BCA 46- 225	46	66	225	13	182	45	55	44	M5A2 (TCMT 110204 CCMT060204)	3
BT 40-BCA 62- 165			165	-	135	-	51	-		3.5
BT 40-BCA 62- 225	62	87	225	11	184	60	62	57		4.5
BT 40-BCA 83- 120			120	-						3.5
BT 40-BCA 83- 165	83	108	165	-						4.5
BT 40-BCA 83- 225			225	-	-	-	63	-	M7A2 (TCMT 160408 CCMT090304)	6
BT 40-BCA 98- 165	98	142	165	-	-	90	83	-	M10A2 (TCMT 160408 CCMT090304)	6