

## Specifications:

Designation	dHS	L	D	L1	L2	L3	G	d1 (Stopper Screw )	Fig
BT30/SL 6/65	6	65	20	15	40	-	M6	M5x16	1
BT30/SL 8/65	8	65	24	15	40	-	M8	M6x18	1
BT30/SL 10/65	10	65	30	16	44	-	M8	M8x25	1
BT30/SL 12/65	12	65	35	20	49	-	M10	M10x30	1
BT30/SL 16/65	16	65	40	23	57	-	M10	M12x30	1
BT30/SLA20/90	20	90	50	25	59	20	M10	M16x30	2
BT30/SLA25/90	25	90	50	25	64	20	M10	M20x30	2
BT40/SL 6/65	6	65	20	15	40	-	M6	M5x16	1
BT40/SL 8/65	8	65	24	15	40	-	M8	M6x18	1
BT40/SL 10/65	10	65	30	16	44	-	M8	M8x25	1
BT40/SL 12/65	12	65	35	20	49	-	M10	M10x30	1
BT40/SL 16/65	16	65	40	23	57	-	M10	M12x30	1
BT40/SLA 20/90	20	90	50	25	59	20	M10	M16x30	2
BT40/SLA 25/90	25	90	50	25	64	20	M10	M20x30	2
BT40/SLA 32/90	32	90	60	30	68	20	M10	M20x30	2
BT40/SLA 40/90	40	90	70	30	78	25	M12	M20x30	2
BT50/SL 6/75	6	75	20	15	40	-	M6	M5x16	1
BT50/SL8/75	8	75	24	15	40	-	M8	M6x18	1
BT50/SL10/75	10	75	30	16	44	-	M8	M8x25	1
BT50/SL12/75	12	75	35	20	49	-	M10	M10x30	1
BT50/SL16/75	16	75	40	23	57	-	M10	M12x30	1
BT50/SLA20/105	20	105	50	25	59	20	M10	M16x30	2
BT50/SLA25/105	25	105	50	25	64	20	M10	M20x30	2
BT50/SLA32/105	32	105	60	30	68	20	M10	M20x30	2
BT50/SLA40/105	40	105	80	30	78	25	M12	M20x30	2

## Note:

- Side Lock Holders with other types of shank like TC, CT, ISO are available on
- Any special sizes can be made to customers request
- Optionally side lock holders can be supplied in balanced condition for high speed applications